

RANGO DE PRINCIPALES PERFILES

| LIMPIAVASTAGOS | | | | | | | | |
|--|---------|------------------------|----------|-------------------|------|--------|-------|--|
| CODIGO | CROQUIS | materiales principales | | Temperat. | | Veloc. | Pres. | |
| | | | | min | max | max | max | |
| | | | | (°C) | (°C) | (m/s) | (MPa) | |
| L01A estándar | | HPU (P2) | | -20 | +115 | 1,0 | | |
| | | NBR (G1) | | -30 | +110 | 1,0 | | |
| | | FKM (G2) | | -20 | +220 | 1,0 | | |
| | | EPDM (G3) | | -45 | +130 | 1,0 | | |
| L01B estándar c/escalón | | HPU (P2) | | -20 | +115 | 1,0 | | |
| | | NBR (G1) | | -30 | +110 | 1,0 | | |
| | | FKM (G2) | | -20 | +220 | 1,0 | | |
| | | EPDM (G3) | | -45 | +130 | 1,0 | | |
| L01C estándar c/frente ángulo | | HPU (P2) | | -20 | +115 | 1,0 | | |
| | | NBR (G1) | | -30 | +110 | 1,0 | | |
| | | FKM (G2) | | -20 | +220 | 1,0 | | |
| | | EPDM (G3) | | -45 | +130 | 1,0 | | |
| L02A estándar c/respaldo | | limpiador | respaldo | | | | | |
| | | HPU (P2) | | POM (R1) METAL | -20 | +115 | 1,0 | |
| | | NBR (G1) | | POM (R1) METAL | -30 | +110 | 1,0 | |
| | | FKM (G2) | | METAL | -20 | +220 | 1,0 | |
| EPDM (G3) | | METAL | -45 | +130 | 1,0 | | | |
| L03A Doble labio | | HPU (P2) | | -20 | +115 | 1,0 | | |
| | | NBR (G1) | | -30 | +110 | 1,0 | | |
| | | FKM (G2) | | -20 | +220 | 1,0 | | |
| | | EPDM (G3) | | -45 | +130 | 1,0 | | |
| L03B doble labio c/escalón | | HPU (P2) | | -20 | +115 | 1,0 | | |
| | | NBR (G1) | | -30 | +110 | 1,0 | | |
| | | FKM (G2) | | -20 | +220 | 1,0 | | |
| | | EPDM (G3) | | -45 | +130 | 1,0 | | |
| L05A Copa | | HPU (P2) | | -20 | +115 | 1,0 | | |
| | | NBR (G1) | | -30 | +110 | 1,0 | | |
| | | FKM (G2) | | -20 | +220 | 1,0 | | |
| | | EPDM (G3) | | -45 | +130 | 1,0 | | |
| L06A banda desliz. c/carg. Aplic media | | limpiador | cargador | | | | | |
| | | PTFE c/mol (T2) | NBR (G1) | -30 | +110 | 10,0 | | |
| | | PTFE c/mol (T2) | FKM (G2) | -20 | +220 | 10,0 | | |
| | | PTFE c/brce (T4) | NBR (G1) | -30 | +110 | 10,0 | | |
| PTFE c/brce (T4) | | FKM (G2) | -20 | +220 | 10,0 | | | |
| L06B banda desliz. c/carg. Aplic liviana | | limpiador | cargador | | | | | |
| | | PTFE c/mol (T2) | NBR (G1) | -30 | +110 | 10,0 | | |
| | | PTFE c/mol (T2) | NBR (G1) | -20 | +220 | 10,0 | | |
| | | PTFE c/brce (T4) | FKM (G2) | -30 | +110 | 10,0 | | |
| PTFE c/brce (T4) | | EPDM (G3) | -20 | +220 | 10,0 | | | |
| L07A Banda deslizante c/carg. doble o'ring | | limpiador | cargador | | | | | |
| | | PTFE c/mol (T2) | NBR (G1) | -30 | +110 | 10,0 | | |
| | | PTFE c/mol (T2) | FKM (G2) | -20 | +220 | 10,0 | | |
| | | PTFE c/brce (T4) | NBR (G1) | -30 | +110 | 10,0 | | |
| PTFE c/brce (T4) | | FKM (G2) | -20 | +220 | 10,0 | | | |